

Walls, Signage and Decals

Product Guide



Cold-Temp is a print media designed for low-temperature applications and features a high-performance adhesive suitable for temperatures below freezing.





Walls, Signage and Decals

Product Guide

What is PV528CT – Cold-Temp?

Printvinyl Cold Temp is ideal for wide-format and screen-printed decals, markings, point-of-purchase displays, durable decals, and indoor or outdoor signage. It is available in a 3.2-mil matte white vinyl that is durable and flexible, with a 90# layflat liner.

PV528CT has an outdoor durability of up to 5 years. It is offered in 150-foot-long rolls with standard widths of 54 or 60 inches, but custom roll sizes and sheets can be accommodated. Sample rolls are also available.

Can be installed at temperatures down to 15 degrees Fahrenheit.
Service temperature range: -65°F to +180°F

Product Code	Face	Adhesive	Liner	Width	Durability	Wall Applications							Recommended Overlaminates	
						Posters	Indoor Signage	Outdoor Signage	POP	Smooth Surface	Tiled Murals	Wall Graphics	Colorgard [®] LUV	Rayzor [™]
PV528CT	 Matte White	Cold-Temp High-Tack	90# Layflat	54", 60"		■	■	■	■	■	■	■	■	■

For a 3.0 mil Gloss Clear vinyl with Cold Temp adhesive, RB599CT is available upon request through your sales representative and is subject to the applicable minimum order quantity (MOQ).

For more information about PrintVinyl CT or other Mactac products, partnerships or graphic solutions, e-mail Mactac.Americas@mactac.com or visit mactac.com/graphics.