

Applications

Fixture & Dispenser Mounting | Acoustic Panel Mounting

Sound Damping | Mirror Mounting

Architectural Detailing | Shiplap & Decorative Paneling

Interior Signage & Display



Fixture Mounting



Acoustic



Sound Damping



Mirror Mounting



General Assembly



Architectural



Interior Signage



- Ultra-strength pressure sensitive adhesive
- Foam and Film Carriers for ease of handling
- Easy Release liner, excellent for all types of installation processes

Benefits

- Ultimate holding power for mounting fixtures, signs or panels with a large profile
- Superior bond to Low VOC paints and low surface energy materials
- Water resistant
- Foam carriers provide excellent cushion between dissimilar surfaces
- Replaces mechanical fasteners





Mactac[®] is a pioneer in 100% solids adhesive technology bringing solutions that stick to the industrial tape and adhesive market since 1959.



Products Featuring Macbond Ultra 555 Adhesive

50°F Minimum App Temperature

Service Range: -0°F to 190°F

Part Number	Carrier	Adhesive mils	Caliper mils	Liner	Standard Master Roll		Performance Characteristics		
		Liner / Unwind	Carrier & Adhesive		Width	Length	Peel SS lbs/sq in	Peel HDPe lbs/sq in	1 kg Shear Hours
IM1763-78	1/32" White PE Faom	2.6 / 2.6	36.45	78# SCK	60"	216'	9	7	1000+
IM1863-78	1/16" White PE Faom	2.6 / 2.6	67.7	78# SCK	60"	108'	8	6	1000+
IB8161-78	0.5 mil PET	1.8 / 1.8	4.1	78# SCK	60"	750'	13.5	8	1000+

Macbond Ultra 555 Products comply with the following:

REACH and RoHS regulations Conflict Minerals

For additional Performance Guides on MacBond Ultra 555 products, please visit www.mactac.com.

Mactac is ISO9000-2015 certified. Mactac is a member of the following organizations:

Gasket Fabricators Association National Association of Graphic and Product Identification Manufacturers, Inc. (GPI) Pressure Sensitive Tape Council (PSTC)

