## **Cleantape® fr**

## **Engineered Tapes & Laminates**















#### Mactac North America announces a new line of Flame Retardant Tapes

- Solvent Free & Non-Halogenated
- Meets UL94 VTM-0
- 100% solids adhesive eliminates harmful solvents. No VOCs or outgassing, reduces CO2 emissions.





**Thermal Runaway** 


Thermal Interface

**Protections** 



# **Cleantape® fr**

## **Engineered Tapes & Laminates**



### **Double-Coated Tapes**



Double Coated Tapes									
			Coat Weight (mils)	Caliper (mils)		Performance Characteristics			
Part Number	Adhesive	Туре	Carrier	Liner/ Unwind	Adhesive & Carrier	Liner	Peel SS lb/in	Tack SS lb/sq.in	Shear hours
FRB4160-72	FR	Acrylic	1.0 mil PET	1.2/1.2	7.7	72#PCK	3.0	4.1	21.8
Transfer Tapes									
			Coat Weight	Caliper (mils)		Performance Characteristics			
Part Number	Adhesive	Туре	Carrier	mils	Adhesive & Liner	Liner	Peel SS lb/in	Tack SS lb/sq.in	Shear hours
FRF4061-72	FR	Acrylic	1.0 mil PET	1.2	6.5	72# PCK	3.0	4.1	21.8
FRF4062-72	FR	Acrylic	1.0 mil PET	2.0	7.3	72# PCK	8.0	6.7	6.2

- Double liner options are available on acrylic products
- Custom constructions are available upon request



- **Application Temperature** 0°F (-18°C) for best performance
- **End Use Temperature** -40°F to 300°F (-40°C to 149°C)\*based on adhesive



Meets UL94 VTM-0



Foam Bonding - Performs well on: EPDM, Nitrile PVC and Poron

For Regulatory Information, please visit www.mactac.com for all product regulatory compliance. For Quality information, please visit www.mactac.com/quality for all manufacturing site ISO 9001 certificates.

For Technical Data Sheets please visit www.mactac.com/industrialtapes.

Mactac is a member of the following organizations: Gasket Fabricators Association Pressure Sensitive Tape Council

