

TECHNICAL DATA SHEET*



mactac.com

Description

Product

Face:

Total Construction

Caliper (Approx): mils

Adhesive:

Liner:

Face

Physical Properties

Caliper
Tensile, lbs/in (YIELD)
Tear
Opacity
Basis Weight 25" x 38"/500

Typical Value

lbs. +/- 10%

Test Method

Adhesive

Physical Properties

90° Peel Adhesion, lbs./in.
 Stainless Steel
 Corrugate
Loop Tack
 Stainless Steel
 Corrugate
Temperature Ranges
Minimum Application Temperature
Service Temperature

Typical Value

lbs / in
lbs / in
lbs / in
lbs / in

Test Method

Disclaimer: Tested with 60# Semi-gloss paper properties at room temperature on standard lab panels. The service temperature listed is subject to limitations of the facestock and substrate used.

Liner

Physical Properties

Caliper, inches
Basis Weight 24"x36"/500

Typical Value

+/- 10%
lbs. +/- 10%

Test Method

Shelf Life One year from the date of shipment, when stored at 72°F and 50% relative humidity.

*This document represents typical values and is not considered a specification.

The user is responsible for determining the product's suitability for all aspects of the application. If there are any questions about applications, or regulatory compliances please contact your Mactac sales representative to discuss your requirements for recommendations. If this is a printed Technical Data Sheet, it is an uncontrolled document. Please check the Mactac website for the latest, most-up-to-date version. The products discussed herein are sold without any warranty as to merchantability or any other warranty, expressed or implied.

Call **1-800-548-3456** for additional product information or visit www.mactac.com

TM Trademark of Morgan Adhesives Company LLC
® Registered Trademark of Morgan Adhesives Company LLC

Revised: