

TECHNICAL DATA SHEET*



mactac.com

Description

Product

Face:

Adhesive:

Liner:

Total Construction

Caliper (Approx): mils

Face

Physical Properties	Typical Value	Test Method
Caliper	+/- 10%	
Tensile, lbs/in (YIELD)		
Tear		
Opacity		
Basis Weight 25"x38"/500	lbs. +/- 10%	

Adhesive

Physical Properties	Typical Value	Test Method
90° Peel Adhesion, lbs./in. Stainless Steel	lbs / in	
Loop Tack Stainless Steel	lbs / in	
Temperature Ranges Minimum Application Temperature Service Temperature		

Disclaimer: Tested with 55# Semi-gloss paper properties at room temperature on standard lab panels. The service temperature listed is subject to limitations of the facestock and substrate used.

Liner

Physical Properties	Typical Value	Test Method
Caliper, inches	+/- 10%	
Basis Weight 24"x36"/500	lbs. +/- 10%	

Shelf Life One year from the date of shipment, when stored at 72°F and 50% relative humidity.

*This document represents typical values and is not considered a specification.

The user is responsible for determining the product's suitability for all aspects of the application. If there are any questions about applications, or regulatory compliances please contact your Mactac sales representative to discuss your requirements for recommendations. If this is a printed Technical Data Sheet, it is an uncontrolled document. Please check the Mactac website for the latest, most-up-to-date version. The products discussed herein are sold without any warranty as to merchantability or any other warranty, expressed or implied.

Call **1-800-548-3456** for additional product information or visit www.mactac.com