

TECHNICAL DATA SHEET*



mactac.com

Description

Product

Face:

Adhesive:

Liner:

**Total Construction
Caliper (Approx):**

mils +/- 10%

Face

Physical Properties

Caliper
Elongation at Break, % (YIELD)
Tensile, lbs/in (YIELD)
Opacity

Typical Value

" +/- 10%

Test Method

Adhesive

Physical Properties

180° Peel Adhesion
Stainless Steel

Typical Value

lbs / in

Test Method

Loop Tack
Stainless Steel

lbs / in

Temperature Ranges

Minimum Application Temperature
Service Temperature

Disclaimer: Tested with 2.6 mil white BOPP film facestock at room temperature on standard lab panels. The service temperature listed is subject to limitations of the facestock and substrate used.

Liner

Physical Properties

Caliper
Basis Weight

Typical Value

" +/- 10%

lbs. +/- 10%

Test Method

Shelf Life One year from the date of shipment, when stored at 72°F and 50% relative humidity.

*This document represents typical values and is not considered a specification.

The user is responsible for determining the product's suitability for all aspects of the application. If there are any questions about applications, or regulatory compliances please contact your Mactac sales representative to discuss your requirements for recommendations. If this is a printed Technical Data Sheet, it is an uncontrolled document. Please check the Mactac website for the latest, most-up-to-date version. The products discussed herein are sold without any warranty as to merchantability or any other warranty, expressed or implied.

Call **1-800-548-3456** for additional product information or visit www.mactac.com