



PERFORMANCE GUIDE

www.Mactac.com

LTC01218

Created: 11/2024 KA

2.0 mil White Gloss Polyester / 805RK / 4.6 mil PCK

Description

Product

LTC01218 - 2 mil gloss top-coated, white polyester with a durable and aggressive permanent acrylic adhesive with optical brightener and a 57# white PCK liner.

Applications and End Uses

Designed for tamper evident labels used in industrial market. Excellent Flexo and thermal transfer printability with most resin ribbons and wax/resin ribbons.

Face

2.0 mil topcoated white gloss polyester film designed for excellent printing, converting, and dispensing. Print test product and consult with your ink supplier to confirm suitability for your application.

Physical Properties without Adhesive

Caliper, inches

0.002 (2.0 mils)

ASTM D-2103

Tensile, lbs./in.

43MD 52CD

JIS K-7127

Adhesive

805RK is high performance, permanent acrylic with optical brightener that has excellent ultimate adhesion. It possesses high chemical and solvent resistance and has very good adhesion to various high and low energy substrates.

Physical Properties of Adhesive

Thickness, inches

0.0009 +/- 10%

180° Peel Adhesion,
lbs./in.

Stainless Steel: 5.1

PSTC-101A (30 min. applied)

Temperature Ranges

Minimum Application

+50°F (10°C)

Service Ranges

-40°F to +212°F (-40°C to +100°C)

CTM #45 Curwood
Polyester Film Dry
Surface

Liner

A 57# white kraft liner, one side is polyethylene laminated. Excellent for die cutting and stripping. The liner is coated with a release system designed for lay-flat application.

Caliper, inches

0.0046 +/- 10%

TAPPI T-411

Basis Weight, lbs. (24" x 36"/500 sheets)

57 +/- 10%

TAPPI T-410

Shelf Life

Product retains its performance and properties for one year from date of manufacture when stored at 72° F and 50% relative humidity.

This product complies with CONEG regulations.

All MACTac Roll Label products meet the requirements of the Clean Air Act of 1990.

*** NOTE: Thermal transfer printing quality and bar code scannability are dependent upon the interworking of several elements; the ribbon, the printhead and the facstock. Please test all applications. Consult MACTac's Technical Marketing Department for guidelines regarding printer and ribbon compatibility.**

CALL 1-800-548-3456 for additional product information

IMPORTANT NOTICE: The information given and the recommendations made herein are based on our research and are believed to be accurate, but no guarantee of their accuracy or completeness is made. In every case, user shall determine before using any product in full scale production, or in any way, whether such product is suitable for user's intended use for their particular purpose under their own operating conditions. User assumes all risk and liability whatsoever in connection with their use of any product. The products discussed herein are sold without any warranty as to merchantability or fitness for a particular purpose, or any other warranty, express or implied. No representative of ours has any authority to waive or change the foregoing provisions, and no statement or recommendation not contained herein shall have any force of effect unless in an agreement signed by the officers of seller and manufacturer. Nothing contained herein shall be construed to imply the nonexistence of any relevant patents or to constitute a permission, inducement or recommendation to practice any invention covered by any patent without authority from the owner of the patent. The following is made in lieu of all warranties, express or implied: Seller's and manufacturer's only obligation shall be to replace or credit such quantity of the product proved to be defective at its discretion.

TM Trademark of Morgan Adhesives Company.

^{*} Registered Trademark of Morgan Adhesives Company.

Tide[®] Registered Trademark of the Procter & Gamble Company

409[®] Registered Trademark of the Clorox Company

