





Roll Label

PSA-coated papers and films in roll-to-roll form. Extensive product options, available customization, varying roll lengths and widths, and customer friendly services, like our Mactac PreciseSM Program, which offers a precise amount of material needed for small runs and limited applications.

www.mactac.com/rolllabel

Trusted Products. Proven Expertise. Real Results.

With Mactac, the Semi-gloss labelstocks you rely on are always within reach—accessible, dependable, and backed by more than 60 years of adhesive expertise.

- Largest Selection 50+ Semi-gloss products tailored to your needs
- Flexibility Low minimum order quantities, starting at just 5,000 feet
- Accessibility Stocked at 11 locations nationwide
- Expert Guidance Dedicated technical centers of excellence to deliver solutions for the most complex applications



PLATINUM[™] Semi-Gloss

The Platinum Brand – Brilliance, Durability and Strength.

Platinum makes your graphics sparkle, gives your labels the robustness needed for today's difficult applications, and keeps your presses running fast and smooth. Platinum is offered in a variety of basis weights and adhesive options giving you a vast selection for your application needs. The Platinum brand of semi-gloss products are the choice for today's flexographic printers.

Product Number	Adhesive	Adhesive Type	Liner	Web Width	Length Ft	Approx. Wt MMSI	FSC^	Precis
		-gloss coated sheet with outstandin			rnal strengt	h character	istics fo	r high
speed printing a	and converting. The shee	et has exceptional smoothness, whit	eness, gloss and opa	city.				
AC2602	640-AT	All-temp Permanent	2.4 SCK	78"	2,500	265#		
AC2692	640-AT OPQ	All-temp Permanent, Block Out	2.4 SCK	78"	2,500	265#		
AC4502	705VHP	High Tack Permanent	2.4 SCK	78"	2,500	265#		
AC5001	Glacier® 733	Freezer	2.4 SCK	60"	2,500	265#		
AC5102	HR-51	Removable	2.4 SCK	78"	2,500	265#		
AC5112LF ⁺	HR-51	Removable	3.2 Kraft	78″	2,500	295#		
AC7002	711VHP	Direct Food	2.4 SCK	78″	2,500	265#		
AC7202	711VHP	Direct Food, Heavy Coat Weight	2.4 SCK	78″	2,500	265#		
AC7802	CHILL AT®	All Temp Permanent	2.4 SCK	78″	2,500	265#		
AC8402	MR840	Ultra Removable	2.4 SCK	78"	2,500	265#		
AC8602	MR860	Removable	2.4 SCK	78"	2,500	265#		
AC9002	710VHP	Permanent	2.4 SCK	78"	2,500	265#		
AC9502	ST-95	Permanent	2.4 SCK	78"	2,500	265#		
AC9512LF ⁺	ST-95	Permanent	3.2 Kraft LF	78"	2,500	295#		
	55# brilliant white sem ting and converting.	ii-gloss coated litho sheet with outst	anding ink receptivity	y and hig	h internal s	trength cha	racteris	tics fo
SGL2602	640-AT	All-temp Permanent	2.4 SCK	78"	2,500	255#		
SGL2692-2	640-AT	All-temp Permanent	1.2 mil PET	78"	2,500	205#		
SGL7002	711VHP	Direct Food	2.4 SCK	78″	2,500	255#		
SGL7092-2	711VHP	Direct Food	2.4 SCK	78″	2,500	255#		
GL7702	CHILL AT FDA	All-temp Permanent	2.4 SCK	78″	2,500	255#		
GL7792-2	CHILL AT FDA	All-temp Permanent	1.2 mil PET	78″	2,500	255#		
GL7802	CHILL AT	All-temp Permanent	2.4 SCK	78"	2,500	255#		
GL7892-2	CHILL AT	All-temp Permanent	1.2 mil PET	78"	2,500	205#		
GL7852-7	CHILL AT	All-temp Permanent	Bloom hi.mpact®	78"	2,500	226#		
GL7902	CHILL AT EXTREME	All-temp High Tack	2.4 SCK	78"	2,500	255#		
GL9002	710VHP	Permanent	2.4 SCK	78"	2,500	255#		
SGL9092-2	710VHP	Permanent	1.2 mil PET	78″	2,500	205#		
GL9502	ST-95	Permanent	2.4 SCK	78"	2,500	255#		
GL9512LF ⁺	ST-95	Permanent	3.2 Kraft LF	78"	2,500	285#		
SGL9592-2	ST-95	Permanent	1.2 mil PET	78″	2,500	255#		
			OLUCK TACK and by		onath ratio			
Wet Strength	54# bright white wet sti	rength semi-gloss construction with	QUICK TACK and nig	gh wet str	engin ratio.	•		
	54# bright white wet sti CHILL AT	rength semi-gloss construction with All-temp Permanent	2.4 SCK	n wet str 78"	2,500	255#		
SGW7802 Platinum Plus	CHILL AT A 50# semi-gloss coate	5	2.4 SCK	78"	2,500	255#	ous	i
SGW7802 Platinum Plus Flexographic, U	CHILL AT A 50# semi-gloss coate	All-temp Permanent ed sheet that has been engineered	2.4 SCK	78"	2,500	255#	ous ■	
SGW7802 Platinum Plus	CHILL AT A 50# semi-gloss coate V Flexographic and UV F	All-temp Permanent ed sheet that has been engineered Rotary Letterpress printing.	2.4 SCK specifically for use as	78" a PS labe	2,500 el stock with	255# In the Aquec		
PLD2692-2	CHILL AT A 50# semi-gloss coate V Flexographic and UV F	All-temp Permanent ed sheet that has been engineered Rotary Letterpress printing. All-temp Permanent	2.4 SCK specifically for use as 2.4 SCK	78" a PS labe 78"	2,500 el stock with 2,500	255# In the Aquect 250#		
SGW7802 Platinum Plus Flexographic, U' PLD2602	CHILL AT A 50# semi-gloss coate V Flexographic and UV F 640-AT 640-AT	All-temp Permanent ed sheet that has been engineered Rotary Letterpress printing. All-temp Permanent All-temp Permanent	2.4 SCK specifically for use as 2.4 SCK 1.2 mil PET	78" a PS labe 78" 78"	2,500 el stock with 2,500 2,500	255# on the Aqueo 250# 234#	ī	

^{*} For more information see MAC3218 Precise/Trimless Guide

⁺ LAY FLAT GUARANTEE Lay flat products are designed for roll-to-sheet applications. They are guaranteed to exhibit lay flat properties of no greater than +/- ½" when evaluating an 8-1/2" x 11" sheet on a flat surface, face-up orientation in a climate controlled (70°F. / 50% R.H.) environment. Lay flat products are supplied on 6" O.D. cores to prevent core related curl. Any products supplied on other than 6" cores are not guaranteed for lay flat against the parameters outlined above.



Complementing the Mactac-branded Platinum Semi-gloss paper offering is the Spinnaker® brand of high quality, prime paper labelstocks. Featuring smooth, mirror-like finishes, and availability with a wide variety of adhesives, Spinnaker is a reliable, trusted solution.

Product Number	Adhesive	Adhesive Type	Liner	Trim	Length 1,000ft	Approx. Wt MMSI	FSC^ Precise	Comments
40# A highly f	flexible semi-gloss t	featuring a very smooth print surfa	ice. Recom	mended	for tight ma	andrel appl	ications.	
47538	BP-52	Acrylic, Permanent	40#	60"	10/5	211#		
47539	ВС-20™	Rubber, Permanent	40#	60"	10/5	209#		
48036	FC-125	Rubber, Permanent	40#	60"	10/5/2.5	209#		
		white sheet featuring high CD tens Print and exceptional gloss make						
48410	CLD-10	Rubber, Permanent	40#	60"	10/5	234#		
42004	SC-21	Rubber, Permanent	40#	60"	10/5/2.5	238#		
		e, semi-gloss litho with excellent st e and liner combinations.	rength and	d print ch	aracteristics	s. It is printa	ble by continu	ious laser when
48567	BP-164	Rubber, Permanent	40#	60"	10/5/2.5	247#		
48573	BP-164	Rubber, Permanent	50#	60"	10/5/2.5	274#		
48561	BP-52	Acrylic, Permanent	40#	60"	10/5	249#		
48584	ВС-20™	Rubber, Permanent	40#	60"	10/5/2.5	247#		
49340	XYZ™(2020)	Acrylic, Permanent	40#	60"	10/5/2.5	244#		
48575	LiftOff™	Rubber, Removable	40#	60"	5/2.5	238#		
48571	GripTight™	Rubber, Heavy Coat Weight	40#	60"	10/5/2.5	253#		
48572	SureLock™	Rubber, Heavy Coat Weight	40#	60"	10/5/2.5	253#		Textured Surfac
48560	B-91	Acrylic, Removable	40#	60"	10/5/2.5	247#		
48562	GPR™	Acrylic, Removable	40#	60"	10/5/2.5	249#		
		gloss sheet engineered to remain h desktop and commercial laser p		d flat afte	r flexo and l	aser printin	g, providing e	asy collating and
42241	BP-52	Acrylic, Permanent	3.2LF	60"	10/5	247#		Laser / Archival
43598	HTR-1	Acrylic, Removable	3.2LF	60"	10/5	247#		
		ho with excellent strength charact ight creates an economical sheet,				with UV and	d water-based	flexo, and UV
49535	ATP^{TM}	Acrylic, Permanent	40#		10/5	255#		
49834	Frostbite™	Rubber, Permanent	40#		10/5	252#		

^{*} For more information see MAC3218 Precise/Trimless Guide

Semi-GlossProduct Offering

